

Dimplex® SOLAR thermal



Solar Pack

The Dimplex Solar package combines all the necessary components needed for a standard installation into easy to purchase kits, with 15 pre-packaged kits available specification and installation is quick and easy.

Combining Dimplex electric heating with Dimplex Solar not only offers low running costs but also provides an excellent solution to meeting part L of the buildings regulations.

Solar Water Heating Products

Cat No.

Solar Collector Kits

SOL200T	2sqm solar collector kit, tiled roof (1 panel)
SOL200S	2sqm solar collector kit, slate roof (1 panel)
SOL200F	2sqm solar collector kit, flat roof (1 panel)
SOL200IT	2sqm solar collector kit, Intergrated roof (1 panel), tile
SOL200IS	2sqm solar collector kit, Intergrated roof (1 panel), slate
SOL400T	4sqm solar collector kit, tiled roof (2 panel)
SOL400S	4sqm solar collector kit, slate roof (2 panel)
SOL400F	4sqm solar collector kit, flat roof (2 panel)
SOL400IT	4sqm solar collector kit, Intergrated roof (2 panels), tile
SOL400IS	4sqm solar collector kit, Intergrated roof (2 panels), slate
SOL600T	6sqm solar collector kit, tiled roof (3 panel)
SOL600S	6sqm solar collector kit, slate roof (3 panel)
SOL600F	6sqm solar collector kit, flat roof (3 panel)
SOL600IT	6sqm solar collector kit, Intergrated roof (3 panel), tile
SOL600IS	6sqm solar collector kit, Intergrated roof (3 panel), slate

Solar Cylinder

unvented cylinder, single solar coil, two immersions		
SCx175SD	175L	2X 3KW
SCx215SD	215L	2X 3KW
SCx255SD	255L	2X 3KW
SCx305SD	305L	2X 3KW
unvented cylinder, solar + auxilliary coils, single immersion		
SCx175SI	175L	3KW
SCx215SI	215L	3KW
SCx255SI	255L	3KW
SCx305SI	305L	3KW

Instantaneous Showers

Cat No.

Aquabatix® Range

ax¹ | Single start/stop temperature dial. Single mode handset for an all over body spray. Three temperature settings. 1.25m chrome effect hose and 530mm riser rail with height adjuster in white.

AX1075C	7.5kW White/Chrome
AX1085C	8.5kW White/Chrome

ax² | Three power settings. With combined on/off function. Numbered temperature dial. Detachable soapdish with gel hanger and combined hose ring. 1.25m chrome effect hose and 530mm riser rail with height adjuster in white.

AX2075C	7.5kW White/Chrome
AX2085C	8.5kW White/Chrome

ax³ | Push button on/off control. Separate power control with three power settings. Numbered temperature dial. Choice of six spray patterns, with rub-clean jets for easy removal of limescale. Detachable soapdish with gel hanger and combined hose ring. 1.25m chrome effect hose and 530mm riser rail with height adjuster in white.

AX3085C	8.5kW White/Chrome
AX3095C	9.5kW White/Chrome
AX3105C	10.5kW White/Chrome

ax³ All Chrome | Push button on/off control. Separate power control with three power settings. Numbered temperature dial. Choice of 6 spray patterns, with rub-clean jets for easy removal of limescale. Detachable soapdish with gel hanger and combined hose ring. 1.25m hose and 530mm riser rail with height adjuster. All chrome finish

AX38.5	8.5kW All Chrome
AX39.5	9.5kW All Chrome
AX310.5	10.5kW All Chrome

ax⁴ | Push button combined power selection and start control with three power settings. Push button off control with phase shut down. Numbered temperature dial. Choice of six spray patterns, with rub-clean jets for easy removal of limescale. Detachable soapdish with gel hanger and combined hose ring. 1.25m chrome effect hose and 530mm riser rail with height adjuster in white.

AX4085C	8.5kW White/Chrome
AX4095C	9.5kW White/Chrome
AX4105C	10.5kW White/Chrome



Electric Central Heating Boiler

Cat No.

Ascari | 12kW modulating electric central heating boiler. No flue required. Maximum power can be reduced to 4kW. Includes:- expansion vessel, expansion relief valve and pump. Style and size to fit alongside kitchen cabinets. Pump and frost protection features.

ASCMA12 12kW electric boiler

Water Heating

SCx Unvented Cylinders | A range of 6 unvented cylinders. CFC free foam injected insulation. 8bar max working pressure. Direct unit has 2x3kW immersions except 80Ltr model which has 1x3kW. Flow rate of up to 55Ltr/min. Indirect units can be heated with gas, oil or electric thermostatically controlled boilers. Pressure tested to 10bar. BBA approved. Guarantee 25 years on cylinder and 5 years on all components except immersion which has 2 years

SCx80i	80L Indirect cylinder
SCx130i	130L Indirect cylinder
SCx150i	150L Indirect cylinder
SCx175i	175L Indirect cylinder
SCx215i	215L Indirect cylinder
SCx255i	255L Indirect cylinder
SCx305i	305L Indirect cylinder
SCx80d	80L Direct cylinder
SCx130d	130L Direct cylinder
SCx150d	150L Direct cylinder
SCx175d	175L Direct cylinder
SCx215d	215L Direct cylinder
SCx255d	255L Direct cylinder
SCx305d	305L Direct cylinder

Unvented Undersink Water Storage Heater | 10 year cylinder guarantee. White coated steel casing. Stainless steel cylinder. No anode to replace. Connects directly to cold mains supply. Stores water up to 68°C. Lockable at lower temperature for handwashing. Thermal cutout set at 85°C.

SUTP7	7L +T&P Valve	H432 x W291 x D286mm
SUTP10	10L+T&P Valve	H488 x W291 x D286mm
SUTP15	15L+T&P Valve	H578 x W291 x D286mm
SUEXK	Expansion Kit	
SUPRK	Pressure Reducing Kit	
SUTP30	30L+Kit	H665 x W400 x D400mm
SUTP50	50L+Kit	H860 x W400 x D400mm
SUTP75	75L+Kit	H1175 x W400 x D400mm

T&P valve for Safety (SUTP only)

Instantaneous Water Heating | Simple to use single on/off temperature control. Compact design.

HM3	3kW H242 x W190 x D102mm
	Open outlet: 200mm swivel arm

Inline Unvented Instantaneous Water Heating | Delivers instant hot water at the point of use. Water can be supplied to one or two outlets. Connects directly to the water mains supply. Small compact shape and no standing heat losses. Choice of two power settings on installation.

IL095	9.5kW H160 x W307 x D74mm
-------	---------------------------

Flat Back Cistern Water Storage Heating | Large vented water storage heaters. Two adjustable thermostat for precise control Overheat protection. 50oC to 80oC Thermostatic control Range. Drain Connection Supplied and Fitted. Cold water storage cistern incorporated in the unit

FB025	3 kW 25L H705 x W470 x D210mm
FB050	3 kW 50L H750 x W600 x D320mm
FB075	3 kW 75L H925 x W600 x D320mm

Wall Mounted Water Boilers | Low voltage electronic controls. High level insulation provide low running costs. Hygienic stainless steel tank. Easy-clean impact resistant plastic case. Removable case for easy maintenance. Safety cut-outs on over temperature and water overflow. 2 year guarantee on parts, and 1 year labour.

WB3	3L	H440 x W310 x D210mm
WB7	7.5L	H485 x W325 x D220mm
WB15	15L	H545 x W350 x D250mm

Economy Wall Mounted Water Boilers | Economy model provides the same safety features as that of the standard range in a similar format and stainless steel case for use where the environment is a little tougher. 1 year parts and labour guarantee.

WB5E	5L	H430 x W285 x D200mm
------	----	----------------------

Oversink Water Heaters |

V5	5L Vented
V10	10L Vented



Ascari
ASCMA12 12kW electric boiler



SCX



SUTP



IL095



FB025



WB5E



HM3



V5